SKU JOURNAL OF ENGINEERING RESEARCH Vol-3 Issue-3
(NATIONAL PEER REVIEWED E-RESEARCH JOURNAL)
(July – September 2026)
E-ISSN 3048-930X

Stability Assessment of Holes in Laminated Composite Circular Plates

[1]Ram Avtar Ahirwar
[2]Shailendra Agrawal
Assistant. Professor
Department of civil engineering
Shri Krishna University, Chhatarpur (M.P.)

ABSTRACT
Comprising two or more components, a composite material has unique features not found in any of its constituent materials. It has advantages mainly because of its high stiffness to weight ratios and high strength to weight ratios. The mechanical properties of the laminated composite material can be varied by suitably changing the lamination scheme. These materials use fibers as the load bearers, and the matrix—which has a low modulus and a high elongation—helps maintain the fibers' integrity while also supplying the necessary flexibility. Fiber-reinforced composites are usually thin plates. They frequently experience compressive loads, which increase the risk of failure when they approach the critical buckling load. Therefore, the researchers' primary focus has always been the composite plates' buckling behavior. The computation of buckling load is important to predict the behavior of structures under dynamic loads. Understanding the buckling characteristics of the constituent elements is essential when designing structures that will be subjected to compressive loading in order to avoid overloading the structure. The primary focus of this study is on annular laminated composite plates' buckling properties. Circular plates with holes will be examined for their stability under buckling. The plates considered are thin plates. To obtain the style forms for various boundary conditions, utilize the ANSYS 13.0 finite element program. We will examine the effects of different parameters on the buckling load, such as fiber orientation, hole location, boundary conditions, number of layers, etc. The outcome of holes sizes as well as that of change in thickness of plates and various other parameters on the buckling load will also be studied.

KEYWORDS
Vibration, buckling, hybrid laminates, FFT, FRF spectrum, FEM etc.

INTRODUCTION

Laminated composite materials are widely used in modern engineering structures due to their superior mechanical properties such as high strength-to-weight ratio, excellent fatigue resistance, and the ability to tailor properties according to design requirements. These materials are extensively used in aerospace, marine,

automotive, and civil engineering applications where lightweight and high-performance structures are essential.

Circular plates made of laminated composites are important structural elements used in components such as aircraft fuselage sections, pressure vessels, turbine covers, and structural panels. In practical engineering applications, these plates often contain holes or cut-outs for purposes such as weight reduction, fastening, inspection access, or integration with other components. However, the presence of these holes introduces stress concentration and significantly affects the overall structural stability.

One of the major concerns in such structures is buckling, which refers to sudden instability under compressive or in-plane loading conditions. The buckling behavior of laminated composite circular plates becomes more complex due to anisotropy, layering sequence, and geometric discontinuities introduced by holes. Factors such as hole size, shape, location, and fiber orientation play a crucial role in determining the critical buckling load and failure mode of the structure.

With the advancement of computational techniques, numerical methods like Finite Element Analysis (FEA) using software such as ANSYS and Abaqus have become essential tools for studying the stability behavior of composite structures. These tools help in predicting deformation patterns, stress distribution, and failure regions with higher accuracy compared to traditional analytical methods.

Therefore, this project focuses on the stability assessment of laminated composite circular plates with holes by analyzing their buckling behavior under various loading conditions. The study aims to understand the influence of geometric and material parameters on structural stability and to develop optimized design guidelines for safer and more efficient composite structures.

Global Status of the theme area of the project

Laminated composite materials have gained significant global importance in aerospace, automotive, marine, and civil engineering industries due to their high strength-to-weight ratio, corrosion resistance, and tailorability of mechanical properties. Circular plates made from such composites are widely used in structural components like aircraft fuselage panels, pressure vessel end caps, turbine components, and marine structures.

Globally, extensive research has been carried out on the stability and buckling behavior of composite plates under various loading conditions. Institutions and industries in the United States, Europe, Japan, and India have focused on improving the predictive accuracy of failure models for composite structures using analytical, experimental, and numerical methods such as Finite Element Analysis (FEA).

A major area of concern in practical applications is the presence of discontinuities such as holes, cut-outs, and openings required for fasteners, inspection, or weight reduction. These holes significantly alter stress distribution and

reduce the buckling strength of the structure. As a result, understanding the stability behavior of perforated laminated composite plates has become an active research topic worldwide.

Advanced computational tools like ANSYS and Abaqus are widely used to simulate complex laminate behaviors, including delamination, stress concentration, and nonlinear buckling. Researchers are also exploring optimization techniques to determine ideal fiber orientation, stacking sequences, and hole geometry to improve structural performance.

Despite considerable progress, challenges remain in accurately predicting post-buckling behavior, damage initiation around holes, and failure under combined loading conditions. Therefore, ongoing global research continues to focus on developing more reliable numerical models and experimentally validated design guidelines for composite structures with cut-outs. This makes the study of stability assessment of holes in laminated composite circular plates a highly relevant and active research area in modern structural engineering National Status of the theme area of the project In India, composite materials research has grown rapidly over the past few decades, driven by increasing demand in aerospace, defense, automotive, and civil infrastructure sectors. Organizations such as the Defence Research and Development Organisation (DRDO), Indian Space Research Organisation (ISRO), Hindustan Aeronautics Limited (HAL), and various Indian Institutes of Technology (IITs) have been actively involved in the development and structural analysis of laminated composite components.

Laminated composite circular plates are commonly used in national applications such as aircraft structural panels, satellite components, pressure vessels, and lightweight mechanical systems. Due to the need for weight reduction and structural efficiency, these components often include holes or cut-outs for fastening, assembly, and functional requirements. However, these openings significantly influence the stability and buckling strength of the structure, making their analysis an important research area in India.

Indian researchers have extensively used analytical methods, experimental testing, and finite element tools like ANSYS and Abaqus to study the buckling and post-buckling behavior of composite plates. Several academic studies from IITs, NITs, and other engineering institutions have focused on optimizing laminate stacking sequences, fiber orientations, and geometric parameters to enhance stability under various loading conditions.

Despite these advancements, challenges still exist in accurately predicting failure mechanisms such as delamination, local buckling around holes, and nonlinear behavior under complex loading conditions. Therefore, ongoing research in India continues to focus on improving numerical modeling techniques and validating results through experimental studies.

Overall, the study of stability assessment of perforated laminated composite circular plates is an important and active research domain in India,

contributing significantly to the advancement of lightweight and high-performance structural design technologies.

Gaps Identified

The analysis of the existing system reveals several gaps that limit its efficiency, usability, and long-term sustainability. One of the major gaps is the reliance on manual processes for data collection and record management. Manual methods are time-consuming, prone to human error, and make it difficult to retrieve information quickly when needed. Another significant gap is the lack of real-time data access. Information is often updated after considerable delays, reducing the accuracy and reliability of reports.

This can affect timely decision-making and overall operational efficiency. In addition, existing systems may not provide adequate integration between different departments, resulting in data duplication, inconsistencies, and communication challenges. Security and privacy are also important concerns. Traditional systems often lack advanced authentication mechanisms, role-based access control, and data encryption, making sensitive information vulnerable to unauthorized access. Furthermore, backup and disaster recovery mechanisms are either weak or absent, increasing the risk of permanent data loss.

Scalability is another limitation. As the volume of users and data grows, existing systems struggle to maintain performance and responsiveness. Many legacy systems are not designed to accommodate future expansion or integration with modern technologies. The user experience also presents a noticeable gap. Complicated interfaces, limited accessibility, and inadequate technical support reduce user satisfaction and productivity. Training requirements for complex systems further increase operational costs and reduce adoption rates.

Finally, there is often insufficient reporting and analytics capability. Decision-makers require accurate, timely, and meaningful insights, but existing systems may provide only basic reports without advanced visualization or predictive analysis.

Identifying these gaps provides a clear understanding of the areas requiring improvement. Addressing these limitations through automation, enhanced security, improved usability, real-time processing, and scalable architecture will significantly improve system performance, reliability, and overall effectiveness.

Finally, there is often insufficient reporting and analytics capability. Decision-makers require accurate, timely, and meaningful insights, but existing systems may provide only basic reports without advanced visualization or predictive analysis.

Identifying these gaps provides a clear understanding of the areas requiring improvement. Addressing these limitations through automation, enhanced security, improved usability, real-time processing, and scalable architecture will significantly improve system performance, reliability, and overall effectiveness.

Bridging the Gaps

Bridging the identified gaps requires the implementation of a modern, technology-driven solution that improves efficiency, accuracy, security, and user experience. The proposed system should automate routine processes, reducing manual effort and minimizing human errors. Automation enables faster data processing, improves consistency, and allows employees to focus on more strategic tasks. To address the issue of delayed information, the new system should support real-time data collection, processing, and reporting. Instant access to updated information enables better monitoring and informed decision-making. Integrating all departments into a centralized database ensures data consistency, eliminates duplication, and improves communication across the organization.

Security improvements should include secure user authentication, role-based access control, data encryption, and regular system backups. These measures protect sensitive information from unauthorized access and ensure business continuity in case of system failures or cyber incidents. Scalability should be incorporated into the system design so that it can accommodate future growth in users, transactions, and data volume without affecting performance. Cloud-based infrastructure and modular system architecture provide flexibility for future upgrades and integration with emerging technologies.

Improving the user interface is equally important. A simple, intuitive, and responsive design enhances user satisfaction, reduces training requirements, and increases overall productivity. The system should also support access from multiple devices, allowing users to perform tasks conveniently from desktops, tablets, or smart phones.

Advanced reporting and analytics features should be included to generate meaningful insights through dashboards, charts, and customizable reports. These capabilities help management monitor performance, identify trends, and make evidence-based

Objectives

- To study the stability of laminated composite circular plates with central and off-center holes.
- To determine the effect of hole geometry on buckling load.
- To analyze different fiber orientations and stacking sequences.
- To perform numerical simulation using ANSYS/Abaqus.
- To validate results using available theoretical/experimental data.
- To identify an optimal design for improved structural stability.

METHODOLOGY

The present study adopts a numerical and analytical methodology to evaluate the stability of laminated composite circular plates containing circular holes. The presence of holes in composite plates significantly alters the stress distribution and reduces the buckling strength. Therefore, a finite element (FE) approach is employed to investigate the influence of hole size, laminate configuration, boundary conditions, and loading

conditions on the structural stability of composite circular plates.

The methodology consists of the following stages:

1. Selection of plate geometry and material properties.
2. Development of laminated composite plate models.
3. Introduction of circular holes with different diameters.
4. Meshing of the plate using suitable finite elements.
5. Application of boundary conditions and compressive loading.
6. Linear eigenvalue buckling analysis.
7. Post-processing of deformation modes, stress distribution, and critical buckling loads.
8. Parametric comparison and interpretation of results.

Typical dimensions may be:

Parameter	Value
Plate Radius (R)	100 mm
Plate Thickness (h)	2–6 mm
Hole Diameter (d)	10–60 mm
Number of Layers	4–16

Geometry of the Composite Circular Plate

A circular laminated composite plate with radius **R** and thickness **h** is considered. A centrally located circular hole is introduced in the plate. Different hole diameter ratios are considered to evaluate their influence on structural stability.

The geometric parameters include:

- Plate radius (R)
- Plate thickness (h)
- Hole diameter (d)
- Hole-to-plate diameter ratio (d/D)

The hole diameter is varied while maintaining constant plate dimensions to investigate the reduction in buckling strength.

Material Selection

Carbon Fiber Reinforced Polymer (CFRP) or Glass Fiber Reinforced Polymer (GFRP) laminates are selected because of their high stiffness-to-weight ratio.

Typical orthotropic material properties are:

Property	Symbol	Value
Longitudinal Modulus	E_1	135 GPa
Transverse Modulus	E_2	10 GPa
Shear Modulus	G_{12}	5 GPa
Poisson Ratio	ν_{12}	0.3
Density	ρ	1600 kg/m³

Each lamina is assumed to be:

- Homogeneous
- Orthotropic
- Linearly elastic
- Perfectly bonded to adjacent layers

Finite Element Modeling

The numerical model is developed using commercial finite element software such as **ANSYS**, **ABAQUS**, or **MSC Nastran**. The modeling procedure includes:

Step 1 Create a circular plate geometry.

Step 2 Introduce a circular hole at the center.

Step 3 Assign composite lay-up.

Step 4 Define orthotropic material properties.

Step 5 Generate finite element mesh.

Quadrilateral shell elements or layered shell elements are used because they accurately model laminated composites. A mesh convergence study is performed to ensure that the critical buckling load does not change significantly with further mesh refinement

EXPECTED OUTCOME

- To analyze the buckling and post-buckling behavior of laminated composite circular plates with different hole configurations.
- To study the effect of hole size, shape, and position on the overall structural stability of the plate.
- To evaluate the influence of laminate stacking sequence and fiber orientation on critical buckling load.
- To develop a numerical simulation model (ANSYS/Abaqus) for predicting stability behavior under different loading conditions.
- To compare numerical results with available analytical or experimental data for validation.
- To determine the optimum design parameters that minimize stress concentration around holes while maintaining structural strength.
- To understand failure mechanisms such as local buckling, delamination, and stress concentration effects in composite structures.
- To contribute to improved design guidelines for aerospace/structural composite components with cut-outs.

Scientific Description

The stability analysis of laminated composite circular plates with holes is based on the mechanics of anisotropic laminated plate theory and structural stability under compressive loading. Composite laminates are typically modeled using Classical Lamination Theory (CLT) or First-order Shear Deformation Theory (FSDT), which account for the directional dependence of material properties across different fiber orientations and layers.

When a circular plate is subjected to in-plane compressive or shear loading, it may lose stability through buckling, which is characterized by a sudden change in deformation mode without significant change in load. The critical buckling load depends on material stiffness matrices (A, B, D matrices in laminate theory), boundary conditions, and geometric parameters.

The introduction of holes in the plate creates discontinuities in the stress field, leading to stress concentration and localized stiffness reduction. These effects significantly influence the global and local buckling behavior. The size, shape, and position of the hole alter the load path and redistribute stresses, often reducing the critical buckling load.

Mathematically, the governing equations are derived from equilibrium conditions and compatibility relations, leading to an eigenvalue problem in linear buckling analysis. The critical load factor is obtained by solving:

[K]{u}=λ[Kg]{u}[K]\{u\} = \lambda [K_g]\{u\}[K]{u}=λ[Kg]{u}

Where [K] is the elastic stiffness matrix, [K_g] is the geometric stiffness matrix, {u} is the displacement vector, and λ represents the critical load multiplier.

Finite Element Analysis (FEA) is widely used to solve this problem numerically due to the complex geometry and anisotropic nature of composites. Software tools such as ANSYS or Abaqus discretize the structure into elements and compute stress distribution, deformation patterns, and eigenvalues for buckling prediction. This study also considers the effect of laminate stacking sequence, fiber orientation, and boundary conditions, which significantly influence the stiffness and stability characteristics. The presence of holes may also trigger local buckling or delamination under high stress gradients, making failure prediction more complex.

Thus, the scientific investigation of this project integrates composite material theory, structural stability analysis, and numerical simulation to evaluate and optimize the performance of perforated laminated composite circular plates.

METHODOLOGY ADOPTED

The methodology adopted for this project is based on numerical simulation using Finite Element Analysis (FEA) to investigate the buckling behavior of laminated composite circular plates containing different hole configurations. The study begins with a detailed literature review to understand existing research on composite plate stability, effects of cut-outs, and gaps in current predictive models. Based on this review, the scope of analysis is defined, focusing on the influence of hole size, location, and laminate orientation on structural stability.

Suitable composite materials such as carbon fiber/epoxy or glass fiber/epoxy are selected, and their orthotropic mechanical properties including Young's modulus, shear modulus, and Poisson's ratio are assigned to each lamina. A circular plate geometry is developed using CAD tools or directly in ANSYS/Abaqus. Variations in the model are introduced by modifying hole size, hole position (central or eccentric), and stacking sequences such as [0/90/0] and [0/45/-45/90].

The finite element model is generated using appropriate shell or solid elements. Mesh refinement is applied particularly around the hole region to capture stress concentration effects accurately. Suitable boundary conditions, such as simply supported or clamped edges, are applied depending on realistic structural constraints. In-plane compressive loads are gradually applied to simulate actual loading conditions.

Linear eigenvalue buckling analysis is performed to determine the critical buckling load and associated mode shapes. The governing eigenvalue problem is solved to obtain load factors corresponding to instability points. Post-processing of results includes evaluation of deformation patterns, stress distribution, and buckling modes.

Finally, a parametric study is conducted by varying geometric and material parameters to understand their influence on stability. The results are validated with available theoretical or published data, and an optimized configuration is suggested for improved buckling resistance and structural efficiency of laminated composite circular plates with holes.

OUTPUT OF THE PROJECT:

- Determination of the critical buckling load for laminated composite circular plates with different hole sizes and positions.
- Development of Finite Element models (ANSYS/Abaqus) for stability analysis of perforated composite plates.
- Generation of stress distribution and deformation contour plots showing the effect of holes on structural behavior.
- Comparison of results for different fiber orientations and stacking sequences to evaluate their influence on stability.
- Identification of the most critical region of stress concentration around holes.
- Analysis of the effect of geometric parameters (hole size, shape, and location) on buckling behavior.
- Validation of numerical results with available theoretical or published research data (if applicable).
- Recommendation of an optimized laminate configuration for improved structural stability.
- Improved understanding of buckling and post-buckling behavior of composite circular plates.
- Preparation of a final project report, presentation, and simulation results suitable for academic evaluation.

CONCLUSIONS

The stability assessment of holes in laminated composite circular plates is an important aspect of structural design, particularly in aerospace, automotive, marine, and other engineering applications where lightweight and high-strength materials are required. The presence of a hole in a laminated composite plate introduces a geometric discontinuity that can significantly influence stress distribution, deformation, buckling behaviour, and overall structural stability.

The study highlights that the stability of laminated composite circular plates depends on several factors, including the hole diameter, plate thickness, fibre orientation, stacking

sequence, material properties, boundary conditions, and loading conditions. The hole may cause stress concentration around its boundary, resulting in localized deformation and a reduction in the overall load-carrying capacity of the plate. The magnitude of these effects depends on the geometric and mechanical characteristics of the composite laminate.

The selection of an appropriate fibre orientation and stacking sequence plays a significant role in improving the structural performance of laminated composite plates. A properly designed laminate can provide better stiffness, improved resistance to deformation, and enhanced buckling stability. Similarly, optimizing the hole-to-plate diameter ratio and maintaining suitable plate thickness can help reduce the adverse effects associated with the presence of holes.

The assessment of critical buckling load and deformation behaviour provides valuable information for determining the structural safety and performance of perforated composite plates. Numerical methods, particularly finite element analysis, can be effectively employed to investigate stress distribution, displacement patterns, and buckling characteristics under different loading and support conditions. Experimental investigations can further validate the numerical predictions and improve the reliability of the analysis. In conclusion, the stability of laminated composite circular plates containing holes can be improved through appropriate geometric design, material selection, and optimization of laminate configuration. A systematic stability assessment is therefore essential for developing safe, efficient, and lightweight composite structures. The findings of this study can contribute to the improved design of perforated laminated composite components and provide a foundation for further research involving multiple holes, different hole geometries, advanced composite materials, and nonlinear buckling behaviour.

Note: This conclusion is written in a general research-paper style. Numerical findings, percentage changes in buckling load, and specific laminate comparisons should be added if you have obtained results from ANSYS, ABAQUS, MATLAB, or experimental testing.

REFERENCES

1. Reddy, J. N. (2004). Mechanics of Laminated Composite Plates and Shells: Theory and Analysis (2nd ed.). CRC Press.
2. Jones, R. M. (1999). Mechanics of Composite Materials (2nd ed.). Taylor & Francis.
3. Timoshenko, S. P., & Gere, J. M. (1961). Theory of Elastic Stability (2nd ed.). McGraw-Hill.
4. Leissa, A. W. (1969). Vibration of Plates. NASA Special Publication 160, National Aeronautics and Space Administration.
5. Whitney, J. M. (1987). Structural Analysis of Laminated Anisotropic Plates. Technomic Publishing Company.
6. Noor, A. K., & Burton, W. S. (1990). Assessment of shear deformation theories for multilayered composite plates. Applied Mechanics Reviews, 43(1), 1–64.