SKU JOURNAL OF ENGINEERING RESEARCH Vol-3 Issue-3
(NATIONAL PEER REVIEWED E-RESEARCH JOURNAL)
(July – September 2026)
E-ISSN 3048-930X

Waste Heat Recovery from Industrial Processes

Swapnil Kumar Singh
Assistant Professor
Department of Mechanical Engineering
Shri Krishna University, Chhatarpur (M.P.)

ABSTRACT

Industrial processes consume large amounts of thermal and electrical energy, and a considerable portion of this energy is ultimately rejected to the surroundings as waste heat. Waste heat is commonly released through hot exhaust gases, furnace surfaces, steam, cooling water, hot products, compressors, engines, and other process streams. Recovering this heat can reduce fuel consumption, improve overall energy efficiency, lower operating costs, and reduce greenhouse-gas emissions. Waste heat recovery (WHR) can be achieved through direct heat exchange, recuperators, waste heat boilers, regenerative systems, heat pumps, Organic Rankine Cycles (ORCs), thermoelectric generators, and other technologies. ORC systems are particularly useful when the available waste heat is at low or medium temperature and can be converted into electricity.

This paper presents an overview of industrial waste heat sources, classification of waste heat according to temperature, major recovery technologies, system components, thermodynamic considerations, applications, benefits, limitations, and future developments. The study also discusses the importance of proper heat-source characterization, heat-exchanger selection, economic analysis, and integration with existing industrial processes. Effective WHR can contribute significantly to energy conservation and sustainable industrial development.

KEYWORDS

Waste Heat Recovery, Industrial Processes, Heat Exchanger, Energy Efficiency, Organic Rankine Cycle, Waste Heat Boiler, Thermoelectric Generator, Energy Conservation.

INTRODUCTION

Energy is one of the most important requirements for modern industrial development. Industries such as steel, cement, glass, chemical processing, petroleum refining, food processing, paper manufacturing, and textile production require substantial amounts of thermal and electrical energy. A large fraction of the supplied energy is used for heating, melting, drying, combustion, evaporation, and other operations. However, not all the supplied energy is converted into useful products.

During industrial operations, energy is continuously rejected in the form of hot gases, steam, hot water, cooling water, heated products, and radiation. This rejected energy is commonly called waste heat. Instead of releasing this heat directly into the environment, it can be recovered and utilized for another useful purpose.

Waste heat recovery is therefore an important energy-conservation technique. It attempts to capture heat from a process and reuse it either within the same process or in another process. The recovered energy can be used for preheating combustion air, heating feed water, producing steam, drying materials, space heating, or generating electricity.

Research has shown that industrial waste heat represents an important opportunity for reducing primary energy consumption and improving process efficiency. In particular, low-temperature industrial waste heat is challenging to reuse directly, making technologies such as ORC systems important for converting otherwise difficult-to-use heat into electricity.

The basic concept of WHR is shown below:

Industrial Process → Waste Heat → Heat Recovery System → Useful Heat/Electricity → Improved Efficiency

The major objective of WHR is not simply to recover the maximum amount of heat, but to recover it economically while maintaining safe and reliable operation of the industrial process.

Sources of Industrial Waste Heat

Industrial waste heat originates from several different sources. The characteristics of waste heat depend on the industrial process, fuel type, equipment, operating temperature, and process conditions.

Exhaust Gases

Furnaces, boilers, kilns, ovens, engines, and gas turbines produce hot exhaust gases. These gases may leave the equipment at temperatures considerably higher than the ambient temperature.

Heat from exhaust gases can be recovered using:

- Economizers
- Air preheaters
- Recuperators
- Regenerators
- Waste heat boilers
- Heat exchangers
- ORC systems

Hot Process Products

Some industrial products leave manufacturing equipment at high temperatures. Examples include:

- Hot steel products
- Glass
- Cement clinker
- Ceramic products
- Metal castings
- Heated chemical products

The sensible heat contained in these products can sometimes be recovered by transferring heat to air, water, or another process fluid.

Cooling Water

Many industrial machines require cooling water. During operation, this water absorbs heat and becomes warm. Instead of rejecting the warm water directly, its heat can be recovered for:

- Feed water preheating
- Space heating
- Process heating
- Domestic hot-water applications
- Heat-pump systems

Steam and Condensate

Steam is widely used in industries for heating and processing. Steam condensate still contains useful thermal energy. Recovering and returning condensate can reduce both energy and water consumption.

Furnace and Kiln Heat

Industrial furnaces and kilns are important sources of high-temperature waste heat. Industries such as steel, cement, ceramics, and glass can recover heat from furnace exhaust gases and hot surfaces.

Engines and Turbines

Internal combustion engines and gas turbines reject heat through:

- Exhaust gases
- Cooling systems
- Lubricating oil
- Charge-air cooling systems

ORC-based systems have been widely investigated for recovering heat from engines and turbines.

ORGANIC RANKINE CYCLE FOR WASTE HEAT RECOVERY

The **Organic Rankine Cycle (ORC)** is one of the important technologies for converting waste heat into electricity. Unlike conventional steam Rankine cycles, ORC systems use organic working fluids with suitable boiling characteristics.

The main components of an ORC are:

1. Pump
2. Evaporator
3. Expander/turbine
4. Condenser

Working Principle

The working fluid is pumped to high pressure and then heated using industrial waste heat. It vaporizes and expands through an expander, producing mechanical power. The expander drives an electrical generator. The vapor is then condensed and returned to the pump.

Simplified Flow

Waste Heat → Evaporator → Organic Fluid Vapor → Expander → Generator → Electricity

ORC technology is especially useful for low- and medium-temperature waste heat. Research literature identifies ORC as a flexible technology capable of using a range of waste-heat temperatures, although performance depends strongly on working fluid, heat-source conditions, cycle configuration, and operating conditions. Recent research also examines regenerative, transcritical, cascade, and other advanced ORC configurations to improve energy and energy performance.

Thermoelectric Waste Heat Recovery

Thermoelectric generators (TEGs) convert a temperature difference directly into electrical energy through the thermoelectric effect.

The basic principle is:

Temperature Difference → Thermoelectric Module → DC Electricity

TEGs have several advantages:

- No moving mechanical parts
- Compact size
- Low mechanical maintenance
- Direct conversion of heat into electricity
- Suitable for distributed waste heat sources

However, thermoelectric systems currently face challenges related to material cost, conversion efficiency, heat-transfer requirements, and long-term durability. Recent research has also examined integration of thermoelectric generators with ORC systems and other waste-heat technologies.

Heat Recovery Using Heat Pumps

Industrial heat pumps can upgrade low-temperature waste heat to a higher temperature that is useful for industrial processes.

For example:

Low-temperature waste heat → Heat Pump → Higher-temperature useful heat

Heat pumps can recover heat from:

- Cooling water
- Wastewater
- Condensers
- Refrigeration systems
- Low-temperature process streams

The major advantage is that heat that is otherwise difficult to use can be upgraded to a more useful temperature.

Economic Analysis

A waste heat recovery project must be economically viable in addition to being technically feasible.

Important economic parameters include:

- Initial investment
- Equipment cost
- Installation cost
- Maintenance cost
- Energy savings
- Electricity savings
- Fuel savings
- Payback period
- Operating cost
- Expected equipment life

Optimization of Waste Heat Recovery Systems

Optimization is necessary to obtain the maximum practical benefit from a WHR system.

Important optimization parameters include:

- Waste-heat temperature
- Waste-heat flow rate
- Heat-exchanger area
- Working-fluid properties
- Operating pressure
- Turbine efficiency
- Pump efficiency
- Condenser temperature
- Pinch-point temperature difference
- Heat-source variability
- Economic parameters

Modern studies increasingly use numerical optimization, process integration, artificial intelligence, machine learning, and advanced control methods to determine suitable operating conditions. For industrial ORC integration, approaches such as pinch analysis, mathematical programming, genetic algorithms, and other optimization techniques have been investigated.

ENVIRONMENTAL IMPACT

Waste heat recovery can provide environmental benefits because it reduces the amount of primary energy required to produce the same industrial output.

Reduced fuel consumption can contribute to lower:

- CO_2 emissions
- NO_x emissions
- SO_x emissions
- Particulate emissions
- Waste thermal discharge

However, the environmental performance of a WHR system should be evaluated over its complete life cycle. Equipment materials, heat exchangers, turbines, working fluids, manufacturing, maintenance, and disposal can all influence overall environmental impact. Recent life-cycle research on ORC systems highlights the importance of component materials, working fluids, and system configuration in determining environmental performance.

FUTURE SCOPE

The future of industrial waste heat recovery is closely related to improved process integration, advanced materials, digital monitoring, and intelligent control.

Important future research areas include:

1. Development of high-performance heat exchangers.
2. Low-cost thermoelectric materials.
3. Advanced ORC configurations.
4. Environmentally friendly ORC working fluids.
5. Hybrid ORC–thermoelectric systems.
6. Integration of WHR with thermal energy storage.
7. AI-based prediction of waste heat availability.
8. Digital monitoring of heat-recovery equipment.
9. Advanced heat pumps for low-temperature waste heat.
10. Integration of WHR with renewable energy systems.
11. Improved corrosion- and fouling-resistant materials.
12. Real-time optimization of industrial heat networks.

The use of cascade and multi-stage systems is another promising direction for recovering heat available at different temperature levels. Recent research also emphasizes combining thermodynamic performance with economic and environmental considerations rather than optimizing only one parameter.

CONCLUSION

Waste heat recovery is an important technology for improving the energy efficiency of industrial processes. A considerable amount of useful thermal energy is rejected from

furnaces, boilers, engines, turbines, kilns, dryers, cooling systems, and other industrial equipment. Recovering this heat can reduce fuel consumption, decrease operating costs, improve overall process efficiency, and support emission reduction. Different WHR technologies are suitable for different temperature levels and industrial conditions. Heat exchangers and recuperators are effective for direct heat recovery, while waste heat boilers can generate useful steam. ORC systems provide an attractive option for converting low- and medium-temperature waste heat into electricity, while thermoelectric generators offer a compact method of direct heat-to-electricity conversion.

However, successful implementation requires careful consideration of heat-source characteristics, equipment cost, fouling, corrosion, process integration, operating variability, and environmental performance. Future WHR systems are expected to become more intelligent through the integration of advanced sensors, artificial intelligence, optimization techniques, energy storage, and improved materials. Overall, waste heat recovery represents an important pathway toward energy-efficient, cost-effective, and sustainable industrial production.

REFERENCES

1. Loni, R., Najafi, G., Bellos, E., Rajaee, F., Said, Z., & Mazlan, M. (2021). A review of industrial waste heat recovery system for power generation with Organic Rankine Cycle: Recent challenges and future outlook. Journal of Cleaner Production, 287, 125070.
2. A review of heat integration approaches for organic Rankine cycle with waste heat in production processes. Energy Conversion and Management, 221, 113175, 2020.
3. Review of organic Rankine cycle (ORC) architectures for waste heat recovery. Renewable and Sustainable Energy Reviews, 47, 448–461, 2015.
4. Mahmoudi, A., Fazli, M., & Morad, M. R. (2018). A recent review of waste heat recovery by Organic Rankine Cycle. Applied Thermal Engineering, 143, 660–675.
5. Generic superstructure synthesis of organic Rankine cycles for waste heat recovery in industrial processes. Applied Energy, 212, 1203–1225, 2018.
6. Ja'fari, M., Khan, M. I., Al-Ghamdi, S. G., Jaworski, A. J., & Asfand, F. (2023). Waste heat recovery in iron and steel industry using organic Rankine cycles. Chemical Engineering Journal, 477, 146925.
7. Environmental and life cycle assessment of organic Rankine cycle technology for industrial waste heat recovery. Journal of Environmental Chemical Engineering, 13(5), 117758, 2025.
8. Modi, C. K., et al. (2026). A review on organic Rankine cycle, thermoelectrics, and process integration in sustainable waste heat recovery technologies. International Communications in Heat and Mass Transfer, 176, 111267.